



Product Service

# Attestation of Conformity

No. E8A 110959 0092 Rev. 01

**Holder of Attestation:** **Guangdong Huasheng Electronic Technology Co., Ltd.**

118# Dongyuan Road, Shipai Town  
523350 Dongguan City, Guangdong Province  
PEOPLE'S REPUBLIC OF CHINA

**Name of Object:** **Power supply  
(LED Driver)**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64760220271202

**Date,** 2024-09-09

( Tony Liu )

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

# Attestation of Conformity

No. E8A 110959 0092 Rev. 01

## Model(s):

HS12A-xxxxxxx-AG, HS12A-xxxxxxx-AB, HS12A-xxxxxxx-CG,  
HS12B-xxxxxxx-CG, HS12B-xxxxxxx-CB, HS12U-050xxx-AG,  
HS12U-050xxx-AB (xxx and yyy are variables, xxx=050-300  
stands for rated output voltage range 5.0-30.0VDC with step of  
0.1V; yyy=010-200 stands for rated output current 0.01-2.0A  
with step of 0.01A.)

## Description of Object:

Rated Input: 220-240VAC, 50/60Hz, 0.4A Max  
Rated Output: See model list for details  
Protection Class: II

Model	Rated output		
	Voltage range (VDC)	Current range (A)	Max. Power (W)
HS12U-050xxx-AG, HS12U-050xxx-AB	5.0	0.01-2.0	10.0
HS12A-xxxxxxx-AG, HS12A-xxxxxxx-AB	5.0-9.0	0.01-2.0	12.0
	9.1-17.0	0.01-1.25	15.0
	17.1-30.0	0.01-0.7	12.0
HS12B-xxxxxxx-CG, HS12B-xxxxxxx-CB HS12A-xxxxxxx-CG	5.0-9.0	0.01-2.0	12.0
	9.1-17.0	0.01-1.33	12.0
	17.1-30.0	0.01-0.7	12.0

## Tested according to:

EN IEC 55015:2019/A11:2020  
EN IEC 61547:2023  
EN IEC 61000-3-2:2019/A1:2021  
EN 61000-3-3:2013/A2:2021